JOHN CULLEN

HAMPTON 25 SURFACE

MINIATURE SURFACE-MOUNTED ADJUSTABLE FLOODLIGHT

LUMINAIRE REF:

PROJECT REF:



The Hampton 25 Surface is a compact IP66-rated floodlight designed for wall washing and general area lighting. Suitable for both interior and exterior use, it combines performance with discreet architectural detailing.

A patented mounting system enables fast, tool-free installation, with secure adjustment at 15° intervals. Optional tamper-proofing available.


Rated IP66, the fitting features alochromed and powder-coated metalwork for long-term performance, including in coastal applications where regular maintenance is recommended.



BRONZE RAL 8019



BLACK RAL 9005





FLOOD

ACCESSORIES



IP66 ENCLOSURE FOR DRIVER LARGE
ACENIPLRG



IP66 ENCLOSURE FOR DRIVER SMALL
ACENIPSML



KEW/HAMPTON 40 CONDUIT BOX
ACHK4CB1



TREE STRAP
ACKHTS1C02

5 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

CE PART L COMPLIANT BRITISH DESIGN UK CA

JOHN CULLEN

HAMPTON 25 SURFACE

MINIATURE SURFACE-MOUNTED ADJUSTABLE FLOODLIGHT

LUMINAIRE REF:

PROJECT REF:


SPECIFICATION	FLOOD
BEAM ANGLE (°)	104°
DRIVE CURRENT (mA)	500
FORWARD VOLTAGE (V DC)	3V
POWER CONSUMPTION (W)	1.5W
LIGHT SOURCE LUMENS (LM)	135.4
LIGHT SOURCE EFFICACY (LM/W)	90
LUMINAIRE LUMENS (LM)	96 LM
LUMINAIRE EFFICACY (LM/W)	30 LM/W
INTENSITY RATING (CD)	32
PART L1 DWELLINGS	YES
PART L2 NON DWELL (DISPLAY)	YES
PART L2 NON DWELL (GENERAL)	NO
MAX TEMPERATURE (°C)	N/A


INGRESS RATING	IP66
IMPACT RATING	N/A
COMPLIANCE	BS EN IEC 60598-1:2014
	IEC 60598-2-7:1982/AMD1:1987/AMD2:1994

COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	94.3
IES TM-30 COLOUR GAMUT (Rg)	98.1
BINNING	2 SDCM (Equivalent)
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +40 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	0-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	350mm
CONNECTOR TYPE	N/A
WEIGHT	50g
FIRE RATED	N/A





5 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

CE PART L COMPLIANT BRITISH DESIGN UK CA