JOHN CULLEN

LUCCA 30

VERSATILE TRIM MICRO UPLIGHT

LUMINAIRE REF:

PROJECT REF:



Lucca 30 is a miniature uplight incorporating ProVent technology to minimise condensation and improve robustness. Fully serviceable and built for the circular economy, it delivers refined uplighting to columns, arches, reveals and walls.

Available with or without a cowl, and in narrow, medium and wide beams. IP67 rated for interior and exterior use, with extended 5 year warranty for interior installations. Fittings come with 1m of cable as standard. Custom cable lengths are available upon request.



WHITE RAL 9910



BLACK ANODISED




BRASS



BRONZE ANODISED




STAINLESS STEEL





NARROW



MEDIUM



WIDE

ACCESSORIES



IP66 ENCLOSURE FOR DRIVER LARGE
ACENIPLRG



IP66 ENCLOSURE FOR DRIVER SMALL
ACENIPSML



LUCCA 30 TRIM BURIAL SLEEVE
ACL3TRS2

3 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

CE PART L COMPLIANT cULus UKCA

JOHN CULLEN


LUCCA 30

VERSATILE TRIM MICRO UPLIGHT

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	NARROW	MEDIUM	WIDE
BEAM ANGLE (°)	11°	20°	36°
DRIVE CURRENT (mA)	350 / 500 / 700	350 / 500 / 700	350 / 500 / 700
FORWARD VOLTAGE (V DC)	3 / 3 / 3	3 / 3 / 3	3 / 3 / 3
POWER CONSUMPTION (W)	1.1 / 1.6 / 2.2	1 / 1.5 / 2.1	1 / 1.5 / 2.1
LIGHT SOURCE LUMENS (LM)	87 / 117 / 153	118 / 160 / 217	118 / 160 / 217
LIGHT SOURCE EFFICACY (LM/W)	79 / 73 / 70	118 / 107 / 103	118 / 107 / 103
LUMINAIRE LUMENS (LM)	55 / 73 / 92	66 / 90 / 119	72 / 97 / 128
LUMINAIRE EFFICACY (LM/W)	50 / 46 / 42	66 / 60 / 57	72 / 65 / 61
INTENSITY RATING (CD)	829 / 1104 / 1401	439 / 600 / 798	178 / 245 / 326
PART L1 DWELLINGS	YES / NO / NO	YES / YES / YES	YES / YES / YES
PART L2 NON DWELL (DISPLAY)	NO / NO / NO	YES / YES / YES	YES / YES / YES
PART L2 NON DWELL (GENERAL)	YES / YES / YES	YES / YES / YES	YES / YES / YES
MAX TEMPERATURE (°C)	40 / 40 / 35	40 / 40 / 35	40 / 40 / 35





TM66	2.4 (LIA Assured Verification Score)
INGRESS RATING	IP65 + IP67
IMPACT RATING	IK08
COMPLIANCE	BS EN 60598-2-13: 2006+A1: 2012+A2: 2016
	BS EN IEC 60598-1:2021
	BS EN 62493:2015+A1:2022
	BS EN IEC 62031:2020+A11:2021


COLOUR TEMPERATURE	2700K
CIE CRI AVAILABLE AS	92 / 98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	92 - 94
IES TM-30 COLOUR GAMUT (Rg)	>98
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	Check individual power ratings

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	0-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched


OTHER DATA	
CABLE TYPE	2 Core Silicone (180°C)
CABLE SIZE	6mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	1000mm
CONNECTOR TYPE	N/A
WEIGHT	N/A
FIRE RATED	N/A











3 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

CE PART L COMPLIANT cULus UKCA