JOHN CULLEN

SQUARE 50 DOWNLIGHT

ARCHITECTURAL DIRECTIONAL DOWNLIGHT

LUMINAIRE REF:

PROJECT REF:



The Square 50 downlight is defined by an ultra-slim bezel and a deep 25 mm dual black baffle, delivering precise light control with minimal glare. Designed for plasterboard, sheetrock and drywall ceilings, it offers up to 35° tilt and full 360° rotation. Available in trim/flange and trimless/flangeless configurations.


The Downlight 50 range features three interchangeable LED engines — Pure 50, AmbiDim 50 and Tune 50 — all supported by a plug-in driver system for effortless, tool-free changes on site.




WHITE RAL 9910



BLACK RAL 9005





SUPER SPOT



SPOT



NARROW



MEDIUM



WIDE



SUPER WIDE

ACCESSORIES



HONEYCOMB INSERT 50MM
ACHC50MM1



PURE 50 OPTIC MEDIUM
ACLE50OPTFME



PURE 50 OPTIC NARROW
ACLE50OPTFNA



PURE 50 OPTIC SUPERWIDE
ACLE50OPTFSW



PURE 50 OPTIC WIDE
ACLE50OPTFWI



SPREADER LENS 50MM
ACLL50MM1

SANDBLASTED GLASS LENS 50MM
ACSG50MM1



SOFTENING LENS 50MM
ACSL50MM2

5 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

PART L COMPLIANT

JOHN CULLEN


SQUARE 50 DOWNLIGHT

ARCHITECTURAL DIRECTIONAL DOWNLIGHT

LUMINAIRE REF:

PROJECT REF:

SPECIFICATION	SUPER SPOT	SPOT	NARROW	MEDIUM	WIDE	SUPER WIDE
BEAM ANGLE (°)	13°	16°	22°	26°	34°	45°
DRIVE CURRENT (mA)	350 MA	350 MA	350 MA	350 MA	350 MA	350 MA
FORWARD VOLTAGE (V DC)	18V DC	36V DC	36V DC	36V DC	36V DC	36V DC
POWER CONSUMPTION (W)	6.6W	12.8W	12W	12W	12W	12W
LIGHT SOURCE LUMENS (LM)	507	998	1344	1344	1344	1344
LIGHT SOURCE EFFICACY (LM/W)	77	78	112	112	112	112
LUMINAIRE LUMENS (LM)	312 LM	710 LM	747 LM	711 LM	661 LM	597 LM
LUMINAIRE EFFICACY (LM/W)	47 LM/W	55 LM/W	62 LM/W	59 LM/W	55 LM/W	50 LM/W
INTENSITY RATING (CD)	3816	6442	4118	3064	1945	1157
PART L1 DWELLINGS	YES	YES	YES	YES	YES	YES
PART L2 NON DWELL (DISPLAY)	NO	NO	YES	YES	YES	YES
PART L2 NON DWELL (GENERAL)	NO	NO	NO	NO	NO	NO
MAX TEMPERATURE (°C)	N/A	N/A	N/A	N/A	N/A	N/A





INGRESS RATING	IP20
IMPACT RATING	IK03
COMPLIANCE	IEC/EN 60598-1:2015
	IEC/EN 60598-2-2:2012

COLOUR TEMPERATURE	2700K,3000K
CIE CRI AVAILABLE AS	98 Ra
IES TM-30 COLOUR FIDELITY (Rf)	95
IES TM-30 COLOUR GAMUT (Rg)	99.4
BINNING	2 SDCM
LIFETIME L70/B10 (HOURS)	>50000
AMBIENT TEMPERATURE (Ta)	-20 ... +35 °C

ELECTRICAL	
SOURCE TYPE	LED
PRODUCT CLASS	Class III (SELV low voltage)
DIMMING PROTOCOL	0-10V dimmable
	DALI dimmable
	Mains dimmable (phase cut dimming)
	Switched

OTHER DATA	
CABLE TYPE	2 Core Silicone (180 °C)
CABLE SIZE	6.4mm OD - 2 off 24/0.2 (0.75mm2)
CABLE LENGTH	350mm
CONNECTOR TYPE	OJ-602B
WEIGHT	760g
FIRE RATED	Yes





5 YEAR WARRANTY

WWW.JOHNCULLENLIGHTING.COM
UK +44 (0) 20 7371 9000 | Middle East & APAC +971 (0) 4 321 114
Europe +33 (0)9 61 68 22 81 | US +1 469 657 4791

© John Cullen Lighting 2026. Technical data figures are for guidance only and are subject to ±5% tolerance
We reserve the right to change the design and specification of our product range without prior notice. E&OE

PART L COMPLIANT