Knightsbridge

DATASHEET



WP21CCT

230V IP65 IK08 21W LED Polycarbonate Wall Fitting - CCT

www.mlaccessories.co.uk

MLA PART CODE	WP21CCT
DESCRIPTION	230V IP65 IK08 21W LED Polycarbonate Wall Fitting - CCT
NET WEIGHT (KG)	0.76
FINISH	Black
CONSTRUCTION	Construction - ABS Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP65
IK RATING	IK08
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	Blind grommet
DIMENSIONS (MM)	Height - 170 Width - 320 Projection - 136
DIFFUSER	Opal
WATTAGE (W)	21
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	1000/1200/1100
LUMENS LIGHT SOURCE ONLY (LM)	2250/2600/2500
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	130
EFFICACY LIGHT SOURCE (LM/W)	135
CIRCUIT WATTAGE (W)	19.5
CCT	3000/4000/6500K
LIGHT COLOUR	CCT
CRI	≥85
SDCM	<6
RUNNING CURRENT (A)	0.106
DISPLACEMENT FACTOR	>0.9

ML ACCESSORIES LTD

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

UK CA CE

SVM	0.012
PST-LM	0.107
BEAM ANGLE (DEGREES)	105
LIFE SPAN (HRS)	25,000
L70B50 LIFESPAN (HRS)	36,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-10~35°C
DRIVER	MAX. OUTPUT - 21W OUTPUT VOLTAGE - 24-42V OUTPUT CURRENT - 500mA ISOLATION - SELV AMBIENT TEMPERATURE (Ta) - 45°C CASE TEMPERATURE (Tc) - 75°C
WARRANTY	3year(s)
MANUFACTURED IN ACCORDANCE WITH	BS EN 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270854251

Date Created: 21/10/2026 11:39

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.