Knightsbridge

DATASHEET



SER3040

SEREN 230V IP40 LED Recessed Tri-Wattage and CCT Downlight - 30/ 35/ 40W

www.mlaccessories.co.uk

MLA PART CODE	**SER3040**
DESCRIPTION	SEREN 230V IP40 LED Recessed Tri-Wattage and CCT Downlight - 30/ 35/ 40W
NET WEIGHT (KG)	1.02
FINISH	White
CONSTRUCTION	Construction - Aluminium Construction 2 - & polycarbonate
CLASS	II
IP RATING	IP40 (IP20 from above)
INPUT VOLTAGE	230V 50Hz
DIMENSIONS (MM)	Diameter - 220 Recessed Depth - 69.5 Minimum Void - 100
CUT-OUT (MM)	Cut-out Diameter - 200
DIFFUSER	Opal
EMERGENCY CONVERSION KIT	EMKIT2LSM
IC RATED	No
WATTAGE (W)	30 / 35 / 40
LAMP TECHNOLOGY	SMD LED
LAMP INCLUDED	Yes
LUMENS (LM)	3665/3460/3600/4275/4230/4130/4710/4745/4900
LUMENS LIGHT SOURCE ONLY (LM)	6510
LUMEN TOLERANCE	10%
EFFICACY (LM/W)	130
EFFICACY LIGHT SOURCE (LM/W)	180
CIRCUIT WATTAGE (W)	36.23
CCT	3000/4000/5000K
LIGHT COLOUR	CCT
CRI	≥80
SDCM	<6
RUNNING CURRENT (A)	0.166

ML ACCESSORIES LTD

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.

UK CA CE

DISPLACEMENT FACTOR	>0.7
SVM	0.01
PST-LM	0.575
BEAM ANGLE (DEGREES)	110
L70B50 LIFESPAN (HRS)	50,000
LED COMPATIBLE	Yes
DIMMABLE	No
OPERATING TEMPERATURE	-25~45°C
WARRANTY	5year(s)
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5056270843811

Date Created: 21/10/2026 11:40

ML Accessories Ltd. reserves the right to withdraw, improve, or modify any design without prior notification.
ML Accessories Ltd. cannot be held responsible for the incorrect application of any product.