

DATASHEET



BATMCW4

230V 4ft 31W Modular CCT and Wattage Adjustable Batten

www.mlaccessories.co.uk

MLA PART CODE	BATMCW4
DESCRIPTION	230V 4ft 31W Modular CCT and Wattage Adjustable Batten
NET WEIGHT (KG)	1.4
FINISH	White
CONSTRUCTION	Construction - Pressed steel Construction 2 - & polycarbonate
CLASS	I
IP RATING	IP20
IK RATING	IK08
INPUT VOLTAGE	230V 50Hz
CABLE GLAND INCLUDED	No
DIMENSIONS (MM)	Length - 1225 Width - 61 Projection - 70
DIFFUSER	Opal
EMERGENCY CONVERSION KIT	MODEMKIT
WATTAGE (W)	17/22/26/31
LAMP TECHNOLOGY	LED
LAMP INCLUDED	Yes
LUMENS (LM)	2500/2600/2600,3100/3300/3200,3600/3900/3700,4100/4500/4300
LUMENS LIGHT SOURCE ONLY (LM)	2700/3000/2800,3500/3900/3600,4100/4400/4200,4700/5200/4800
LUMEN TOLERANCE	5%
EFFICACY (LM/W)	160
EFFICACY LIGHT SOURCE (LM/W)	173/172/169/163
CIRCUIT WATTAGE (W)	17.1/22.2/26.1/31.8
CCT	3000/4000/5700K
LIGHT COLOUR	CCT
CRI	≥85
SDCM	<6
RUNNING CURRENT (A)	0.090/0.10/0.12/0.14

SVM	0.01
PST-LM	0.02
BEAM ANGLE (DEGREES)	120
L70B50 LIFESPAN (HRS)	50000
DIMMABLE	No
OPERATING TEMPERATURE	-20~45°C
DRIVER	DRIVER TYPE - Constant Current MAX. OUTPUT - 40W OUTPUT VOLTAGE - 50-133V OUTPUT CURRENT - 200/250/300/350mA POWER FACTOR - 0.95 EFFICIENCY FULL LOAD - 90 CASE TEMPERATURE (Tc) - 80°C
WARRANTY	7year(s)
MANUFACTURED IN ACCORDANCE WITH	BS 60598
ORIGIN OF MANUFACTURE	China
DECLARATION OF CONFORMITY (HELD ON FILE)	Yes
EAN	5061061272824

Date Created: 22/10/2026 13:25

