orluna


one mini adjustable

origin natural




one mini adjustable
origin natural

circular product









Unit height increases by 12mm / 0.48in for SPOT and both ELLIPTICAL BEAMS

ORLUNA LED Technologies Limited,
Unit C, Holly Industrial Park,
Ryan Way, Watford,
Hertfordshire WD24 4YP
United Kingdom

info@orluna.com

+44 (0) 1923 889 712

orluna

one mini adjustable
origin natural

circular product

1 When an old Orluna light comes to the end of its life, or is faulty, instead of throwing it away, we kindly ask you to return it to us.

2 Once we've received the unwanted or faulty fitting, it's dismantled, repaired and renewed with a new LED and PCB.

3 The fully repaired and tested product enters back into our stock –with a brand new warranty.

4 The 'new' light fitting is despatched to a new customer.







ORLUNA LED Technologies Limited,
Unit C, Holly Industrial Park,
Ryan Way, Watford,
Hertfordshire WD24 4YP
United Kingdom

info@orluna.com

+44 (0) 1923 889 712

orluna

one mini adjustable
origin natural

circular product

2700K

		SPOT	CRISP		SOFT	SPECIALITY	
LIGHT VALUES		Spot	Medium	Wide	Wash	Elliptical	Elliptical
	Beam Width FWHM	15°	18°	30°	35°	10×45°	20×40°
	Initial Lumens	521	521	521	521	521	521
	Engine Lumens	207	462	462	417	222	290
	Luminaire Lumens	148	283	265	236	87	101
	Initial Lm/CW	90	90	90	90	90	90
	Luminaire Cd	1706	1984	909	589	310	589

POWER	Voltage	33.4V
	Drive Current	155mA
	Circuit Power (typ)	5.8W

3000K

		SPOT	CRISP		SOFT	SPECIALITY	
LIGHT VALUES		Spot	Medium	Wide	Wash	Elliptical	Elliptical
	Beam Width FWHM	15°	18°	30°	35°	10×45°	20×40°
	Initial Lumens	567	567	567	567	567	567
	Engine Lumens	236	483	475	442	192	176
	Luminaire Lumens	148	299	278	248	105	125
	Initial Lm/CW	98	98	98	98	98	98
	Luminaire Cd	1849	2200	1000	615	328	610

POWER	Voltage	33.4V
	Drive Current	155mA
	Circuit Power (typ)	5.8W

Binning SDCM (Hot)	2
CRI (typ)(R9)	98 (99)
TM30 Rf Rg	Rf 97.7 Rg 100.4
Lifetime (TM21)	L90 B5 50,000hrs (inc driver)
Lifetime (Calculated)	L70 426,000hrs

DRIVER	Protocols	Mains Dim / DALI / 0-10V / Non-dim
	Dim to Dark	0.1% Lux
	Distance from LED	20m / 65' (series wiring)
	Emergency	Emergency packs available

27/02/26

SPECIFICATION CODE

Engine type	Bezel	Colour Temp	Driver	Beam Width	Bezel Colour	Baffle Colour	Options
NL	**ONEM**	**27**	**M**	**M**	**W**	**BB**	**F 54**
		27 / 2700K 30 / 3000K 40 / 4000K*	**M / Mains Dim** D / DALI 0 / 0-10v N / Non Dim X / No Driver	**M / Medium** W / Wide T / Soft S / Spot L / Elliptical Linear O / Elliptical Oval	**W / White RAL 9010** D / White RAL 9003 B / Black RAL 9005 C / Other RAL V / Dark Bronze* T / Medium Bronze* R / Light Bronze* Y / Burnished Brass* G / Polished Brass K / Brushed Chrome L / Polished Chrome Z / Other Metallic	WB / White RAL 9010 DB / White RAL 9003 **BB / Black RAL 9005** CB / Other RAL VB / Dark Bronze TB / Medium Bronze RB / Light Bronze YB / Burnished Brass GB / Polished Brass KB / Brushed Chrome LB / Polished Chrome ZB / Other Metallic	**F / 60 min Fire Rated Plate** **54 / IP54** 65 / IP65 P / Sea & Spa IP65 C / Constant Torsion*1 H / Honeycomb N / Frosted Lens Z / LSZH Cable K / Click Connector F- / 60 min Fire Rated Hoody

*NOTE:increase 3000k by 7%

* - Fire Rated Hood must be used with Dark Bronze, Medium Bronze, Light Bronze and Burnished Brass Bezels
*1 - NOTE: Fire Hood if used with constant torsion springs.

ORLUNA LED Technologies Limited,
Unit A, Chiltern Park Industrial Estate,
Dunstable, LU5 4LT
United Kingdom

info@orluna.com

+44 (0) 1923 889 712

orluna