

UK/EU G9 2000-3000K

3.6W | 360 lm | 2000-3000K
G9-4W-2000-3000-RA97-240V





IES/LDT photometry files
and product photography
available on request



PHYSICAL

Bulb dimension:	18mm
Bulb length:	57mm
Glass shape:	T18
Base:	G9
Materials:	Ceramic & Polycarbonate
Glass finish:	Lightly frosted
Weight:	18g
Max. working temp.:	Max. 40°C
IP rating:	IP20

ELECTRICAL

Power:	3.6W
Current:	0.2 A
Voltage:	12VDC/AC
Frequency:	50/60Hz
Power factor	0.9
Efficiency:	100 lm/W
Lifetime:	15,000 hrs

ILLUMINATION

CCT:	2000-3000K
Lumens:	360 lm
Incandescent equiv.:	48 W
Flicker:	<5%
Beam angle:	360°
Light source:	LED
CRI:	97Ra
R9:	97
TM30 - Rg	100
TM30 - Rf	90

DIMMING

Dimmable 0-100%
Recommended dimmer: Tala Rotary Wall Dimmer
(For a full list of recommended and compatible dimmers see website)

Tala Energy Ltd. 25b Vyner Street,
London, E2 9DG, United Kingdom

Tala Europe B.V. Bertus Aafjeshove 40
Nieumwegein 3437 JN

tala.co.uk | hello@tala.co.uk | +44 7700 170343724-8111

WARRANTY

2 years

EAN

5061046299303

Specification subject to change without notice. Refer to our website for the most recent product documentation. Tala designs in the EU/UK are protected by registered and or unregistered design rights